ElectroMax®
WE ARE JUST MAKING LIGHTING RIGHT



Galaxy

24 LED Linear Projector

Image not found or type unknown

MADE IN ROMANIA

OSRAM LED TECHNOLOGY INCLUDED

TÜV SÜD

CE

RoHS Compliant

ElectroMax®
WE ARE JUST MAKING LIGHTING RIGHT

GALAXY



APPLICATION



Commercial Residential Public Architectural

This product can be used successfully in various applications in different fields:

- Garden lighting
- Facade lighting

Technical specifications

Casing material	Anodized aluminum
Casing color	GRAY Other colors available on demand
Light diffuser	Clear polycarbonate
Power supply	Standard 230V AC 12-24V AC/DC
Number of LEDs	24
Power / LED	1W 2.5W
Total power	24W 60W
Driver	Included (Inside the body case)
COD PRODUS	LO-014

Description

- This modern architectural LED projector is ideal for special architectural lighting effects and is suitable for mounting on building facades. Because of the very long life span of the LEDs, the projector is virtually maintenance-free.
- Designed and manufactured in Romania

Photometric characteristics

- Color rendering index: 80 for WN and WW and 70 for WH
- Focus is done with specially designed lenses in order to obtain the desired light angle. The lenses can have a narrow, medium or wide focus.
- The luminous flux depends on the LED's colour. For the white colour it has a min. value of 100 lm/W, whether it is warm white, neutral white or cool white.

Technical specifications

- The casing is made of anodized aluminium.

- The diffuser is made of 3 mm thick UV protected clear polycarbonate
- The mounting system is made of anodized aluminium.
- The LED projector can be rotated to the angle desired by the user.
- The LED projector has the CE marking and are manufactured according to RoHS.

Electrical characteristics

- Standard power supply 230V AC, 50/60Hz, optional at 12 or 24V DC
- The power consumption of the network is 24 or 60 watts depending on the power consumed by the LEDs. One of these options can be chosen.
- Electrical safety class I
- Power cord length: 2m

Operating environment

- The ingress protection rating is IP 66.
- Rated operating temperature from -20 °C up to +40 °C.
- The impact protection rating is IK 10.

Dimensional characteristics

- 610 x 54 x 115 mm
- Weight 2,5kg

Focus



Narrow focus (N)



Medium focus (M)



Wide focus (W)



Street focus (S)

Tel. +40 254 515 465
Fax +40 254 546 114

http://www.electromax.ro
e-mail: electromax@electromax.ro